Good. Safe. Yellow.

Abrasive mop

SM 611



Klingspor Schleifsysteme GmbH & Co. KG Hüttenstraße 36 · 35708 Haiger · Germany

Fon + 49 (0) 2773 922-0 · Fax + 49 (0) 2773 922-186 sales@klingspor.de · www.klingspor.de



SM 611



Structure

Grain	Aluminium oxide	
Grinding flaps	LS 309 X	
Bonding	Resin	
Core	Metal side flange+ synthetic resin	

Application

Material	Paint/varnish/filler, wood, plastic, metals		
Application	Finishing of all kinds of surfaces		
Machine	Flexible shaft grinder and straight grinder (up to 0200 mm), stationary grinding machine, robotic		
	systems		

Market segment

- ► Achieving of very smooth surfaces with low surface roughness.
- ► Aluminium oxide cloth flaps with ideal combination of aggressivity and wear behaviour. Best benefit concerning perfor-mance and lifetime by using with a recommended speed between 35 and 42 m/s.
- ► Good adap-tability of the flaps to the contours of the workpiece.
- ► High safety for the user due to special mounting system with mounting plates SMD 612 (fitting in the groove of flaps and flanges)

Diameter in mm	Width in mm	Grit	Max. RPM
100	30,50	40-180	9.500
140	25,50	60-120	6.500
165	25,30,50	40-320	5.800
200	25,50	40-120	4.800
250	25,30,50	60-320	3.800
300	50	40-320	3.200