
# Good. Safe. Yellow.

Klingspor Abrasive Paper

PS 33 BK/CK



# **PS 33 BK/CK**



### **Grit sizes**

12	16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
					V		<b>√</b>	V	<b>√</b>	✓	<b>√</b>	V	V	V	<b>√</b>	<b>√</b>		<b>√</b>	<b>√</b>	<b>√</b>					

### **Structure**

Grit	Aluminium oxide
Coating	Semi-open
Bonding	Resin
Backing	C-paper (grit 40-120), B-paper (grit 150-600)
Production width	1.250 mm
Other	Self-fastening
Delivery form	Discs, strips

## **Application**

Material	Paint/Varnish/Filler, wood, plastic
Application	Rough, intermediate and finish sanding of flat and curved surfaces
Machines	Orbital sander, hand sanding, delta sander

# **Market segment**

Automotive repairing, wood and furniture industry and trade, plastic mould constructions, especially formed parts out of glass fibre reinforced plastics (e.g. windmill blades, boatbuilding,...)

### **Product utility**

Increased sanding performance and high aggressiveness because of special annealed aluminium oxide grain. High flexibility but also good stability and tear resistance because of lateximpregnated B-, respectively C-weight paper backing. Available in numerous dimensions and hole pattern for all common machines.