

Good. Safe. Yellow.

Kronenflex® cutting-off wheels

A 930 N



Klingspor Schleifsysteme GmbH & Co. KG
Hüttenstraße 36 · 35708 Haiger · Germany
Fon +49 (0) 2773 922-0 · Fax +49 (0) 2773 922-186
sales@klingspor.de · www.klingspor.de



A 930 N

Quality

SPECIAL

Bond	■ ■ ■ ■ □ □ □
Aggression	■ ■ ■ ■ ■ ■ ■ ■
Service life	■ ■ ■ ■ ■ ■ ■ □

Properties

Grain	Aluminium oxide
Bond	Soft

Application



Recommended materials	Steel, stainless steel, aluminium, castings
Machines	Transportable chop saw (<3 KW)

Market segment

- ▶ Maintenance and repair work
- ▶ Steelwork
- ▶ Metal fabrication
- ▶ Plant construction

Advantages

- ▶ Large cutting-off wheel with soft bonding for universal usage on chop saws.
- ▶ In comparison to the A 30 N Special, which has two glass fibre layers, the A 930 N Special wheel has only one glass fibre layer in the middle, whereby the cutting performance is increased significantly due to less side friction, advantageous especially when used on low-powered machines.
- ▶ No clogging of the disc periphery because of the soft bonding system, at the same time very aggressive cut with minimal burr formation.
- ▶ Highest aggressivity and lifetime of the disc used on chop saws up to 3 KW engine power.
- ▶ Manufactured and certified according to European Standard EN 12413 and oSa regulations.

Diameter x Width x Bore in mm	Form	Max. operating speed	Max. RPM	Cat. number
300 x 2,5 x 25,4		80 m/s	5.100 rpm	322627
350 x 3 x 25,4		80 m/s	4.400 rpm	322628