

Good. Safe. Yellow.

Kronenflex® cutting-off wheels

A 946 TZ



Klingspor Schleifsysteme GmbH & Co. KG
Hüttenstraße 36 · 35708 Haiger · Germany
Fon +49 (0) 2773 922-0 · Fax +49 (0) 2773 922-186
sales@klingspor.de · www.klingspor.de



A 946 TZ

Quality

Bond	■■■■■■■■■
Aggression	■■■■■■■□
Service life	■■■■■■■■■

Properties

Grain	Aluminium oxide
Quality	Special
Bond	Resin, fiber-reinforced

Application








Recommended materials	Stainless steel, steel, NF metals, casting
Machines	Angle grinders of all performance classes

Market segment

- ▶ Maintenance and repair work
- ▶ Steelwork
- ▶ Metal fabrication
- ▶ Plant construction

Advantages

- ▶ Extra long service life across all applications
- ▶ Short cutting times
- ▶ For universal use in metal processing
- ▶ Less Burr formation
- ▶ Delivered in Kronenflex Box
- ▶ Free of iron, sulfur and chlorine

Diameter x Width x Bore in mm	Form	Max. operating speed	Max. RPM	Cat. number
100 x 1,6 x 16		80 m/s	15,300 rpm	339103
115 x 1,6 x 22,23		80 m/s	13,300 rpm	339109
125 x 1,6 x 22,23		80 m/s	12,200 rpm	339110
150 x 1,6 x 22,23		80 m/s	10,200 rpm	339111
180 x 1,6 x 22,23		80 m/s	8,500 rpm	339112
230 x 1,9 x 22,23		80 m/s	6,600 rpm	339113
230 x 1,9 x 22,23		80 m/s	6,600 rpm	339114