

**MANILLE DROITE – Type commercial**


RÉF. 5235

Acier zingué - Coefficient de sécurité 1/5

CODE	A	B	D	F	G	H	I
CMU (kg)	70	100	250	400	630	750	1000
diam D (mm)	5	6	8	10	12	14	16
A (mm)	10	12	16	20	24	28	32
H (mm)	19	25	32	38	51	53	64
poids (kg)	0,01	0,02	0,06	0,12	0,20	0,32	0,48

CODE	K	L	M	N	O	P	Q
CMU (kg)	1600	2000	2500	3150	4000	6000	8000
diam D (mm)	20	22	24	28	32	38	42
A (mm)	40	44	50	56	64	76	84
H (mm)	76	89	100	115	127	152	185
poids (kg)	0,94	1,26	1,85	2,60	3,88	6,50	7,8

TYPE COMMERCIAL



**MANILLE LYRE – Type commercial**

RÉF. 5255

Acier zingué - Coefficient de sécurité 1/5

CODE	A	B	D	F	G	H	I	J
CMU (kg)	80	100	200	300	500	600	800	1000
diam.D (mm)	5	6	8	10	12	14	16	18
A (mm)	10	12	16	20	24	28	32	37
C (mm)	18	18	24	30	36	42	48	55
H (mm)	20	24	32	40	48	56	64	73
poids (kg)	0,015	0,027	0,063	0,12	0,21	0,34	0,5	0,6

CODE	K	L	M	N	O	P	Q
CMU (kg)	1100	1500	2000	2600	3200	4500	6000
diam. D (mm)	20	22	25	28	32	38	42
A (mm)	40	44	50	56	64	76	84
C (mm)	60	66	75	84	96	114	142
H (mm)	80	88	100	112	128	152	185
poids (kg)	0,98	1,31	1,92	2,7	4,03	6,74	8

TYPE COMMERCIAL

