

MANILLE DROITE – Standard


RÉF. 5230

Acier estampé zingué
Coefficient de sécurité 1/5

CODE	AG	BG	DG	FG	GG	HG	IG	JG	KG
CMU (kg)	70	100	250	400	600	800	1000	1300	1600
d (mm)	5	6	8	10	12	14	16	18	20
C (mm)	4	5	6,5	8	9,5	11	13	14,5	16
E (mm)	10	12	16	20	24	28	32	36	40
H (mm)	21	25	33	42	50	57	61	65	70
poids (kg)	0,013	0,022	0,05	0,092	0,17	0,26	0,34	0,49	0,67

CODE	LG	MMG	NG	OG	PG	QG	RG	SG
CMU (kg)	2000	2800	3150	4000	5000	6300	7100	8000
d (mm)	22	25	27	30	33	36	39	42
C (mm)	17,5	19	27	30	33	36	39	38
E (mm)	44	48	54	60	66	72	78	60
H (mm)	74	80	89	99	103	111	126	131
poids (kg)	0,9	1,22	2,15	2,83	3,7	4,8	6	7,4

ESTAMPÉE



MANILLE LYRE – Standard

RÉF. 5250

Acier estampé zingué / Coefficient de sécurité 1/5

CODE	AG	BG	DG	FG	GG	HG	IG	JG
CMU (kg)	80	100	200	300	500	600	800	1250
d / C (mm)	5	6	8	10	12	14	16	18
H (mm)	20	24	32	40	48	56	64	82
E (mm)	10	12	16	20	24	28	32	35
D (mm)	16	20	24	33	39	46	46	52
poids (kg)	0,019	0,034	0,07	0,13	0,26	0,4	0,5	0,71

CODE	KG	LG	MMG	NG	OG	PG	QG	RG
CMU (kg)	1100	1500	2000	3150	4000	5000	6300	7100
d / C (mm)	20	22	25	27	30	33	36	39
H (mm)	80	88	100	120	118	128	143	153
E (mm)	40	44	50	54	60	66	72	78
D (mm)	65	72	81	80	89	100	106	113
poids (kg)	0,8	1,3	2,00	2,42	3,23	4,25	5,70	7,1

ESTAMPÉE

