



SERRE-CÂBLE à étrier « Estampé à chaud »
Marquage CE

RÉF. 5274

ESTAMPÉ A CHAUD

Semelle et étrier ACIER



CODE	A	B	C	D	E	F	G	H	I	K	L	M	N	P	Q	R	S	T	V
câble Ø mm	3-4	5	6	8	10	11	12	14	16	18	20	22	24	28	30	32	38	45	50
A en mm	21	25	30	33	38	40	45	46	53	59	60	64	70	80	80	92	95	115	115
D en mm	M4	M5	M6	M6	M8	M8	M10	M10	M10	M12	M12	M12	M12	M14	M14	M16	M16	M16	M16
L en mm	20	24	34	34	44	45	55	55	63	78	78	81	86	110	112	115	130	158	158
Poids en kg	0,01	0,02	0,03	0,04	0,07	0,08	0,12	0,14	0,18	0,26	0,29	0,30	0,38	0,56	0,71	0,91	1,03	1,45	1,45



SERRE-CÂBLE à étrier – INOX

RÉF. 5285


**Acier INOX
AISI 316**

position correcte des serre-câbles
étriers sur brin mort, semelles sur brin tirant

brin mort
→ charge (brin tirant)



CODE	A	B	BA	C	D	E	F	G	H	I	J	K	L	M	N
câble Ø mm	2	3-4	5	6	8	10	12	14	16	18	20	22	25	28	32
C (mm)	10	8	9	11	12	14	16	18	20	21	22	23	24	30	37
D (mm)	3	4	5	6	6	8	10	10	10	12	12	12	12	14	16
H (mm)	18	22	24	33	35	43	54	54	65	80	80	85	85	105	110
L (mm)	18	22	24	30	33	37	45	46	53	55	58	64	69	80	92
largeur semelle (mm)	10	14	16	18	20	22	25	27	30	31,5	33	34	39	42	46
Poids (kg)	0,01	0,01	0,02	0,03	0,04	0,07	0,12	0,15	0,2	0,24	0,27	0,31	0,36	0,60	0,90



INOX AISI 316

