

M-LT-550

HYDRAULIC LIFTING TABLES

Lifting table for intensive use - Load capacity 550 KG

This mobile lifting table is a practical and economical way to lift and move heavy loads in heights from 330 mm to 980 mm.

The goods are placed at the optimum height with a hydraulic foot pump (double speed).

The hydraulic components are of very high quality.

The lever can be removed manually.

The descent speed is adjustable by a manual damper.

The type 550 has a safety valve mounted on the pump that is activated in the event of an overload or breakage of a hydraulic element, the table falls smoothly.

This speed control valve is a unique descent speed protection and prevents sudden collapse due to hose damage.

At the push bar side 2 swivel wheels with foot protection and double brake, at the front 2 fixed wheels.

The wheels are equipped with ball bearings and solid rubber tires. Wheel dimensions: 150x40mm.

Finished in gray lacquered steel.

Scissor tables in accordance with NEN EN 1570 standard and CE-Marking requirements.

Delivery completely assembled (excluding the push bar and foot pump lever).



11350
M-LT-550



Safety valve in case of overload

- * Table suitable for intensive use.
- * Safety valve in case of overload prevents the table from collapsing.
- * At the push bar side 2 swivel wheels with foot protection and double brake, at the front 2 fixed wheels.

Cap. (kg)	Platform LxB (mm)	Table height min/max. (mm)	Dimensions LxWxH (mm) Unfolded	Dimensions LxWxH (mm) Folded	Weight (kg)	Number of pedal strokes	Article	Art.nr.
550	900x600	330 / 980	1150x600x900	1150x600x420	83	51 (* 30)	M-LT-550	11350