

**M-LT-
WH300-15**

HYDRAULIC LIFTING TABLE DOUBLE SCISSORS 300kg

Lifting table with double scissors for intensive use - Load capacity 300 KG

This mobile lifting table is a practical and economical way to lift and move heavy loads in heights from 410 mm to 1500 mm.

The goods are placed at the optimum height with a hydraulic foot pump (double speed).

The hydraulic components are of very high quality.

The lever can be removed manually.

The descent speed is adjustable by a manual damper.

The type WH300-15 has a safety valve mounted on the pump that is activated in the event of an overload or breakage of a hydraulic element, the table falls smoothly.

This speed control valve is a unique descent speed protection and prevents sudden collapse due to hose damage.

At the push bar side 2 swivel wheels with foot protection and double brake, at the front 2 fixed wheels.

The wheels are equipped with ball bearings and solid rubber tires. Wheel dimensions: 150x42mm.

Finished in gray lacquered steel.

Scissor tables in accordance with NEN EN 1570 standard and CE-Marking requirements.

Delivery completely assembled (excluding the push bar and foot pump lever).



11360
M-LT-WH300-15



- * Table suitable for intensive use.
- * Safety valve in case of overload prevents the table from collapsing.
- * At the push bar side 2 swivel wheels with foot protection and double brake, at the front 2 fixed wheels.



Safety valve in case of overload

Cap. (kg)	Platform LxW (mm)	Table height min/max. (mm)	Dimensions LxWxH (mm) Unfolded	Dimensions LxWxH (mm) Folded	Weight (kg)	Number of pedal strokes	Article	Art.nr.
300	900x600	410 / 1500	1180x600x900	1180x600x490	120	63 (* 38)	M-LT-WH300-15	11360