

Service carts



Comfortable, maneuverable and stylish shelved trolley with fiberglass reinforced PP shelves

Frame of extruded aluminum.

2 sturdy shelves made of fiberglass reinforced polypropylene.

Phthalate free, suitable for food contact.

Shelves resists temperatures of +140,5°C and -20°C.

Platforms tested according to ISO and ASTM standard.

Equipped with 4 swivel wheels, 2 with brakes.

Castors are made of TPR (thermoplastic rubber) and non-marking.

Rides very smoothly through the swivel wheels with ball bearings.

Castors resists temperatures of +90°C and -20°C

Loading capacity complete cart 250Kg.

Applicable in many environments such as maintenance, healthcare, medical and food sector.



12481
HX-808LE-Black



12523
HX-808LE-3 Grey

- * Frame of extruded aluminum.
- * 3 sturdy shelves made of glasfiber reinforced polypropylene.
- * Equipped with 4 swivel wheels, 2 with brakes.
- * Loading capacity complete cart 250Kg.

Cap. (kg)	Cap. per platform (kg)	Number of shelves	Dim. platform LxWxH (mm)	Dimensions LxWxH(mm)	Distance between platforms	Weight (kg)	Swivel Wheel Ø (mm)	Color	Article	Art. nr
250	125	2	915x520	1100x520x950	553	15	100 (4")	Black	HX-808LE	12481
250	125	2	915x520	1100x520x950	553	15	100 (4")	Grey	HX-808LE-3	12523