

DYNAMOVIS-1

Tournevis dynamométrique DYNAMOVIS de 0,6 à 1,5 Nm



SERRAGE CONTRÔLÉ

Description

Dynamic screwdriver DYNAMOVIS " green ring " identifying the clamping range from 0.6 Nm to 1.5 Nm.

Produit conforme aux normes

ISO 6789

NF ISO 6789-1

ACCURACY:

Accuracy guaranteed at +/- 6%.

Single-direction disengaged screwdriver, right-hand tightening.

No adjustment of the tightening torque possible by the operator.

Screwdriver numbered and delivered with a calibration certificate in accordance with NF EN ISO 6789.

Length (without blade): 157 mm.

Length (with blade): 193 mm.

Diameter: 33 mm.

Type II - Class D.

Blades sold at retail, interchangeable covering all areas of use.

Données techniques

Référence	DYNAMOVIS-1	Capacité	0,6 - 1,5 Nm
Entraînement	6 Pans creux 1/4"	L (mm)	157
D (mm)	33	Poids (kg)	0,18
Garantie			

Découvrez tous nos produits dans nos catalogues en ligne



Les outils Indispensables SAM 2021

[Consulter le catalogue](#)



Outillage 2021

[Consulter le catalogue](#)



Automobile 2021

[Consulter le catalogue](#)



Pneumatique 2021

[Consulter le catalogue](#)



Sécurité anti-chute 2020

[Consulter le catalogue](#)