


PBD PEEL 4.0/4.8



PBD4.0-4.8FICHE

For installation information please refer to the tooling overview and manuals on our website www.scell-it.com
 Pour les conditions de pose, merci de vous référer à la description de l'outil et aux manuels disponibles sur notre site web.
 Angaben zur Verarbeitung entnehmen Sie bitte der Geräteübersicht und den Betriebsanleitungen auf unserer Website.
 Pro informace ohledně montáže navštivte naše webové stránky nebo nahlédněte do manuálu k nářadí.

ENGLISH	FRANÇAIS	DEUTSCH	CZECH
Mandrel : Steel	Tige : Acier	Dorn : Stahl	trn : Ocel
Body : Aluminium	Corps : Aluminium	Körper : Aluminium	dfik : Hliník
Dome head black	Tête plate laquée noir	Flachrundkopf schwarz	plochá hlava černá



PART NO/REF	D ₁	L	D ₂	K	D ₃	P	G
	Ø (mm)	(mm)+1.0 / -0.2	Ø (mm)	(mm)	Ø (mm)	mini (mm)	min-max (mm)
PBD4012	4.0 +0.08 / -0.15	12.0	8.0 -0.3 / +0.3	1.40 -0.3 / +0.0	2.20	27	4.0-6.5
PBD4016		16.0					8.0-11.0
PBD4020		20.0					12.0-15.0
PBD4812	4.8 +0.08 / -0.15	12.0	9.5 -0.3 / +0.3	1.50 -0.3 / +0.0	2.70	27	2.0-6.0
PBD4816		16.0					6.0-10.0
PBD4820		20.0					10.0-14.0
PBD4825		25.0					16.0-19.0

			
D ₁ (mm)	(N)	(N)	Ø (mm)
4.0	1 270	1 150	4.2
4.8	1 855	1 600	5.0

UNIT PLANT CERTIFICATES



ISO 9001:2000
TS 16949

Scell-it®
Engineering & Development

© 2009 Blue future Intellectual Proterities

Data shown are subject to change without prior notice as a result of continuous product development and improvement policy.
 Your local Scell-it representative is at your disposal should you need to confirm latest information.