


WAK CLOSED END 3.2/4.0/4.8

For installation information please refer to the tooling overview and manuals on our website www.scell-it.com
 Pour les conditions de pose, merci de vous référer à la description de l'outil et aux manuels disponibles sur notre site web.
 Angaben zur Verarbeitung entnehmen Sie bitte der Geräteübersicht und den Betriebsanleitungen auf unserer Website.
 Pro informace ohledně montáže navštivte naše webové stránky nebo nahlédněte do manuálu k nářadí.




WAK3.2-4.8FICHE

ENGLISH	FRANÇAIS	DEUTSCH	CZECH
Mandrel : Steel	Tige : Acier	Dorn : Stahl	trn : Ocel
Body : Aluminium	Corps : Aluminium	Körper : Aluminium	dfik : Hliník
Countersunk head	Tête fraisée à 120°	Senkkopf	zapuštěná hlava



PART NO/REF	D ₁	L	D ₂	K	D ₃	P	G
	Ø (mm)	(mm)+1.0 / -0.2	Ø (mm)	(mm)	Ø (mm)	mini (mm)	min-max (mm)
WAK3207	3.2 +0.08 / -0.10	7.5	6.0 ±0.4	-	1.7	26	1.5-3.0
WAK3209		9.0					3.0-4.5
WAK3212		12.0					6.0-7.5
WAK4009	4.0 +0.08 / -0.15	9.5	7.5 ±0.5	-	2.2	27	2.5-4.5
WAK4012		12.5					6.5-8.0
WAK4014		14.0					8.0-9.5
WAK4809	4.8 +0.08 / -0.15	9.5	9.0 ±0.5	-	2.6	27	3.0-4.5
WAK4812		12.5					6.0-7.5
WAK4814		14.0					7.5-9.0
WAK4815		15.5					9.0-10.5
WAK4819		19.0					10.5-14.0



D ₁ (mm)	(N)	(N)	Ø (mm)
3.2	1 070	1 245	3.3
4.0	1 710	2 240	4.1
4.8	2 230	3 070	4.9

UNIT PLANT CERTIFICATES



ISO 9001:2000
TS 16949

Scell-it®
Engineering & Development

© 2009 Blue future Intellectual Proterities

Data shown are subject to change without prior notice as a result of continuous product development and improvement policy.
 Your local Scell-it representative is at your disposal should you need to confirm latest information.